

TEST REPORT

1. Applicant

* Client Name : KH-FEELUX Co. Ltd.
* Address : 235-48 Gwangjeok-ro Gwangjeok-myeon Yangju-si Gyeonggi-do 482-844 Korea
* Date of Receipt : 210804

2. Purpose of Report :

3. Number of Report :

4. Test Standard / Item : / 210804 DVP-24V-C90-R-5000K

5. Test Period : 210804 ~ 210804

6. Test Environment

* Ambient Temp. : 00.0 +- 3 °C
* Relative Humidity : 00.0 +- 10 % RH

7. Test Item

* Name of Product :
* Rating :
* Model :

8. Test Result : Refer to the attachment

Confirmation	Test by	JSY	Sign	Technical manager	JSY	Sign

* The result shown in this test report refer only to the sample(s) tested unless otherwise stated.

* This report cannot be reproduced, except in full.

* This report is for reference only. It cannot replace the report by standard organization(s).

Result

Report Number	Sample Name	Sample Number	Test Standard
Test Item	Unit	Result	Notice
Beam Distribution Test		See Attachement	
ATHD	%	0.0	
CIE 1931 Cx, Cy		0.3529 , 0.3647	
Correlated Color Temperature	K	4767	
Ra		90.84	
Power Factor		1.000	
Input Voltage	V	24.000	
Input Current	A	0.110	
Input Watt	W	2.63	
Lamp Flux	lm	205	
Efficient	lm/W	77.65	
luminous Intensity (Max , Center)	cd	432 , 432	
Illuminance	lx	432	1 m
		108	2 m
		48	3 m

* This test result is for the sample provided by the client.

* Sample photo

Click to load image

Luminaire

Lamp

No. of lamps 1

Voltage (V) 24

Report

Lamp flux (lm) 205

Current (A) 0.11

Filename 210804 DVP-24V-C90-R-5000K.jdt

Total flux (lm) 205


Power Factor 1

Operator

Date

2021-08-04 오후 2:16:10

Luminous Intensity Distribution



Luminaire

Lamp

No. of lamps 1

Voltage (V) 24

Report

Lamp flux (lm) 205

Current (A) 0.11

Filename 210804 DVP-24V-C90-R-5000K.jdt

Total flux (lm) 205


Power Factor 1

Operator

Date

2021-08-04 오후 2:16:10

Luminous Intensity Distribution (Lowest 10%)



Luminaire

Lamp

No. of lamps	1	Voltage (V)	24	Report
Lamp flux (lm)	205	Current (A)	0.11	Operator
Total flux (lm)	205	Power Factor	1	Date 2021-08-04 오후 2:16:10

Luminous Intensity Data

Maximum (cd) : 432

Minimum (cd) : -1

G/C	0	5	10	15	20	25	30	35	40	45	50
0	414.99	413.92	413.04	411.23	413.13	409.68	411.56	410.2	410.04	412.08	411.19
5	370.64	370.87	373.5	374.15	376.88	378.18	380.16	381.92	384.91	386.5	391.53
10	308.23	308.7	313.32	315.64	320.09	320.93	325.92	326.64	333.36	336.15	342.28
15	235.1	235.43	240.53	241.09	247.39	247.81	253.08	256.03	261.97	264.85	273.36
20	163.07	163.17	167.76	168.36	173.3	173.37	179.37	180.81	186.53	188.07	195.24
25	100.14	99.65	103.6	103.18	107.23	107.37	112.35	112.5	117.14	117.22	122.52
30	42.5	42.71	45.83	45.34	48.26	48.19	51.18	50.83	54.07	54.16	58.33
35	18	18.75	19.26	18.7	19.9	20.25	20.1	20.26	21.33	22.45	23.52
40	9.87	9.08	9.61	9.35	9.23	9.16	10.6	10.1	10.37	9.97	11.58
45	5.08	5.05	4.76	4.57	4.42	4.21	5.29	4.72	5.65	5.46	5.36
50	2.61	1.58	2.79	2.26	2.19	3.21	2.67	1.85	2.94	2.93	2.9
55	1.15	0.96	1.25	0.68	0.96	1.26	0.85	1.22	0.9	1.69	1.15
60	0.05	1.29	0.58	1.41	0.55	0.76	0.87	0.69	-0.17	0.67	1.36
65	0.41	0.22	-0.15	-0.34	0.5	-0.89	-0.09	0.36	0.22	0.94	0.03
70	0.12	-0.72	0.23	0.54	-0.06	0.53	0.07	-0.01	-0.39	0.43	0.6
75	-0.17	0.48	-0.52	-0.03	-0.6	-0.21	-0.02	-0.01	0.56	-0.64	-0.33
80	0.12	-0.05	-0.21	0.27	-0.11	-0.39	0.22	0.39	-0.54	0.06	-0.73
85	0.36	-0.37	-0.16	-0.65	-0.83	-0.26	-0.18	0.21	-0.01	0.26	-0.33
90	0.19	-0.08	-0.04	0.58	-0.02	-0.07	0.39	0.02	0.46	0.11	-0.3
95	0.21	-0.06	-0.35	-0.19	0.34	-0.57	0.29	-0.27	0.26	-0.15	-0.07
100	0.99	0.13	-0.29	0.29	0.35	0.21	0.35	0.2	0.18	-0.76	-0.35
105	0.42	-0.15	-0.17	-0.24	-0.61	0.12	0.62	-0.03	1	0.36	-0.14
110	0	0.65	-0.06	-0.24	-0.12	0.32	0.44	0.42	0.2	0.53	-0.13
115	0.02	0.34	0.08	0.14	1	0.25	0.08	-0.32	0.75	0.23	-0.24
120	-0.09	0.11	-0.17	0.34	0.42	0.12	0.76	0.27	0.38	0.4	0.34
125	0.32	0.62	0.49	0.75	0.33	-0.06	0.13	0.55	0.03	1	0.61
130	0.52	0.73	1.26	0.8	0.88	0.71	-0.13	0.15	0.3	0.34	0.43

Luminaire

Lamp

No. of lamps	1	Voltage (V)	24	Report
Lamp flux (lm)	205	Current (A)	0.11	Operator
Total flux (lm)	205	Power Factor	1	Date 2021-08-04 오후 2:16:10

Luminous Intensity Data (Continued)

Maximum (cd) : 432

Minimum (cd) : -1

G/C	55	60	65	70	75	80	85	90	95	100	105
0	410.89	409.98	411.21	410.13	411.29	410.77	410.89	411.14	413.8	407.21	412.47
5	387.73	394.49	396.12	399.39	401.8	404.89	407.53	410.23	415.43	413.05	416.69
10	346.58	350.44	354.73	359.89	363.61	367.77	371.04	378.05	379.78	382.18	386.01
15	276.87	279.38	284	292.18	294.76	301.95	303.88	309.45	311.91	319.51	321
20	196.94	205.18	205.21	212.26	215.24	221.81	223.67	230.8	233.55	237.69	237.96
25	123.02	130.21	131.87	136.46	138.28	144.4	145.7	150.67	152.34	156.34	156.57
30	59.37	63.76	64.05	69.47	70.31	74.66	75.1	80.31	80.6	83.66	82.94
35	23.67	25.34	26.87	28.89	29.68	32.43	33.64	35.73	36.66	38.89	38.49
40	11.57	12.81	11.15	13.94	13.96	16.07	16.72	17.5	17.81	19.66	18.75
45	5.91	5.26	6.37	6.89	7.14	7.69	8.26	9.44	9.22	10.2	8.96
50	2.54	2.66	2.18	3.7	2.89	3.95	3.57	3.59	4.07	4.26	4.04
55	1.01	1.44	1.92	1.19	1	1.57	1.2	1.85	1.72	1.28	1.74
60	0.01	0.26	0.41	0.56	0.59	1.21	1.33	1.5	1.11	1.23	0.54
65	0.6	0.51	1.04	0.66	0.52	0.75	0.44	1.02	0.32	0.43	0.36
70	0.24	0.28	0.11	0.14	-0.64	0.01	0.07	0.12	0.28	-0.14	0.5
75	-0.02	-0.08	-0.16	0.37	0.22	0.11	-0.32	0.46	0.21	0.18	0.3
80	0.17	0.26	-0.06	-0.02	-0.53	0	-0.01	0.22	-0.08	-0.04	-0.49
85	0.37	-0.07	0.18	0.41	0.26	-0.27	-0.13	-0.23	-0.78	0.13	-0.21
90	0.52	-0.22	-0.14	0.22	-0.12	-0.63	0.4	-0.09	0.14	-0.31	-0.27
95	-0.21	-0.48	-0.79	0.56	0.3	0.25	-0.28	-0.19	-0.3	0.39	-0.23
100	0.12	0.77	0.16	-0.1	0.25	-0.39	0.5	0.63	-0.13	-0.58	0.3
105	0.04	0.28	0.23	0.15	0.48	0.45	-0.94	0.15	-0.52	0.96	0.01
110	0.15	-0.3	-0.21	-0.21	0.07	0.1	0.65	-0.39	0.33	-0.11	-0.41
115	0.54	0.01	-0.12	-0.27	0.34	0.6	-0.01	0.27	0.36	-0.39	0.39
120	0.24	0.66	0.46	0.34	0.67	0.4	0	-0.04	0.23	-0.04	0.69
125	0.3	0.18	0.22	0.36	0.11	0.33	0.45	0.01	-0.04	0.5	0.52
130	0.78	1.31	0.24	0.49	0.32	0.6	0.92	0.47	0.27	0.7	0.52

Luminaire

Lamp

No. of lamps	1	Voltage (V)	24	Report
Lamp flux (lm)	205	Current (A)	0.11	Operator
Total flux (lm)	205	Power Factor	1	Date 2021-08-04 오후 2:16:10

Luminous Intensity Data (Continued)

Maximum (cd) : 432

Minimum (cd) : -1

G/C	110	115	120	125	130	135	140	145	150	155	160
0	411.31	412.92	412.22	414.85	414.09	416.02	412.65	415.7	413.97	415.58	413.48
5	417.25	418.82	420.28	424.02	422.58	424.83	425.26	425.08	425.06	426.23	426.3
10	389.19	392.4	395.13	392.39	397.46	397.52	400.25	397.26	400.45	399.81	401.43
15	325.89	326.55	331.1	331.11	335.41	335.15	337.94	337.03	338.65	336.76	339.26
20	244.74	243.41	249.19	248.17	251.26	253.18	256.33	253.66	257.51	254.81	257.27
25	160.74	160.62	165.09	162.63	167.2	165.23	168.48	167	171.11	167.63	168.73
30	85.36	84.58	86.53	84.53	87.12	85.36	87.82	86.1	89.58	87.67	89.37
35	39.92	38.69	40.57	38.81	40.19	39.08	40.8	40.43	42.65	42.07	44.22
40	19.86	18.51	18.99	18.16	19.14	18.51	19.74	19.57	20.53	20.89	22.33
45	9.83	9.09	9.21	8.25	9.08	8.37	8.84	8.59	9.17	9.9	9.44
50	3.93	3.98	3.75	3.72	3.71	4.28	4.1	4.02	3.78	3.9	4.62
55	1.45	1.17	1.56	1.49	1.82	1.85	1.69	1.7	1.89	2.34	2.09
60	0.48	0.99	0.53	0.62	0.92	1.26	1.16	1.3	1.49	1.16	1.47
65	0.59	0.71	0.43	1	0.41	0.19	0.92	1.02	0.98	1.07	0.6
70	0.17	-0.2	0.38	0.15	0.05	-0.08	0.01	0.26	-0.06	-0.33	-0.03
75	-0.31	-0.17	0.77	-0.33	0.26	-0.37	0.26	-0.48	-0.27	-0.21	0.64
80	-0.39	0.38	0.24	-0.02	-0.11	0.23	0.48	0.18	-0.02	-0.22	-0.67
85	0.99	0.28	0.43	0.63	0	-0.16	-0.06	-0.07	0.07	0.21	-0.23
90	0.31	-0.93	-0.33	-0.18	0.14	0.26	0.09	0.55	0.28	-0.42	-0.21
95	-0.04	-0.09	-0.15	0.24	-0.17	0.24	0.32	0.2	0.19	-0.32	0.45
100	-0.37	0.04	-0.18	0.64	0.89	0.34	-0.2	-0.42	0.3	-0.06	-0.3
105	0.09	0.89	0.05	0.19	-0.4	-0.74	-0.19	0.19	-0.33	0.14	0.43
110	-0.05	-0.47	0.53	1.45	0.38	0.03	0.39	0.03	-0.74	0.06	0.22
115	0.52	0.23	-0.29	-0.49	0.09	0.7	-0.37	-0.11	0.33	0.51	0.95
120	0.29	0.7	0.34	0.26	0.27	-0.07	0.34	0.23	0	0.31	-0.12
125	0.22	0.66	0.54	-0.02	0.33	1.08	0.64	0.81	0.48	0.2	0.51
130	0.45	-0.01	0.15	1.06	0.48	-0.3	0.92	1.11	0.43	0.52	0.31

Luminaire

Lamp

No. of lamps	1	Voltage (V)	24	Report
Lamp flux (lm)	205	Current (A)	0.11	Operator
Total flux (lm)	205	Power Factor	1	Date 2021-08-04 오후 2:16:10

Luminous Intensity Data (Continued)

Maximum (cd) : 432

Minimum (cd) : -1

G/C	165	170	175	180	185	190	195	200	205	210	215
0	416.89	414.39	414.64	414.99	413.92	413.04	411.23	413.13	409.68	411.56	410.2
5	421.54	427.13	422.72	432.32	429.19	425.57	424.23	419.87	418.83	413.12	411.55
10	399.09	396.64	393.31	412.8	409.99	405.5	401.93	395.66	392.64	384.73	381.93
15	336.38	337.09	332.45	355.48	355.16	346.48	341.97	336.47	330.96	324.14	319.05
20	253.22	254.71	249.63	273.38	271.92	265.01	260.87	252.93	249.17	242.39	238.91
25	166.89	168.24	162.93	185.85	184.11	177.17	173.79	167.36	165.42	157.67	155.15
30	88	88.07	85.33	102.52	101.64	94.67	93.12	87.02	84.86	79.04	78.59
35	44.21	45.63	43.71	51.62	50.28	46.81	45.03	41.46	40.52	37.21	36.51
40	22.5	23.38	23.21	27.34	26.17	23.63	23.08	20.56	19.82	18.05	16.65
45	10.01	10.65	10.68	12.42	11.87	11.4	10.52	9.99	9.11	8.21	7.35
50	4.15	4.85	4.05	5.04	5.41	4.84	4.79	3.01	4.37	3.93	3.76
55	2.39	2.55	2.28	2.11	2.94	2.31	2.24	1.8	2.1	1.89	2.21
60	0.78	1.44	1.64	1.86	1.4	0.94	1.16	1.78	1.34	0.86	0.45
65	1.11	1.1	0.95	1.05	0.57	0.88	0.78	0.56	0.83	-0.32	0.27
70	0.62	0.28	0.16	0.92	0.13	0.71	-0.58	0.51	-0.15	0.26	0.61
75	-0.06	0.59	-0.36	0.05	0.36	0.35	-0.6	-0.24	-0.05	0.09	-0.4
80	0.13	0.01	-0.04	0.49	0.08	-0.44	-0.17	0.59	0.65	-0.42	-0.04
85	0.03	-0.15	-0.18	-0.65	-0.01	0.19	0.43	0.4	-0.2	-0.72	0.05
90	-0.09	-0.56	-0.69	-0.18	0.4	-0.24	0.45	0.23	-0.44	0.1	0.22
95	0.01	0.45	-0.39	0.24	-0.08	0.15	0.24	0.61	-0.56	0.4	0.2
100	-0.03	-0.41	-0.5	-0.22	-0.87	-0.1	0.18	0.35	0.52	0.1	-0.16
105	0.13	0.04	0.57	-0.32	0.78	-0.43	0.01	-0.23	-0.37	-0.76	0.29
110	0.59	0.39	-0.01	0.41	0.07	0.21	0.27	0.06	0.21	0.18	0.38
115	0.4	0.75	0.67	-0.55	0.51	0.21	-0.14	-0.16	-0.2	-0.05	-0.06
120	0.02	-0.01	0.01	-0.21	0.32	0.34	-0.11	-0.44	0.12	0.01	0.31
125	0.34	-0.08	0.01	0.72	0.61	0.31	0.14	-0.46	0.31	0.09	0.94
130	0.4	0.71	0.38	0.79	-0.09	0.34	0.12	0.71	0.57	0.79	0.44

Luminaire

Lamp

No. of lamps	1	Voltage (V)	24	Report
Lamp flux (lm)	205	Current (A)	0.11	Operator
Total flux (lm)	205	Power Factor	1	Date 2021-08-04 오후 2:16:10

Luminous Intensity Data (Continued)

Maximum (cd) : 432

Minimum (cd) : -1

G/C	220	225	230	235	240	245	250	255	260	265	270
0	410.04	412.08	411.19	410.89	409.98	411.21	410.13	411.29	410.77	410.89	411.14
5	407.12	405.44	402.19	401	397.79	394.85	390.77	388.76	384.26	384	381.48
10	373.52	371.03	365.44	360.22	354.93	352.03	344.59	343.02	335.39	332.66	327.28
15	311.13	306.88	298.29	295.43	285.37	283.52	276.8	272.89	266.47	263.77	257.8
20	230.37	225.93	220.28	217.1	209.79	205.58	199.55	198.19	189.41	189.98	183.05
25	147.99	145.66	139.48	137.95	131.39	128.93	123.06	122.15	117.12	116.59	111.25
30	73.45	72.11	68.61	68.27	63.41	63.85	58.67	58.04	54.17	53.85	49.82
35	34.32	34.02	32.7	31.92	30.63	29.86	28.2	27.69	25.47	25.47	23.84
40	16.81	16.38	15.88	15.43	14.89	15.65	14.68	14.49	12.82	13.11	11.72
45	7.25	6.93	7.32	7.27	6.82	7.27	6.34	6.81	6.62	6.25	5.27
50	3.07	3.19	3.02	3.66	2.98	3.05	2.91	2.96	2.43	2.71	2.76
55	1.28	1.34	1.49	1.6	1.52	1.58	1.62	2.11	1.55	0.71	0.97
60	1.47	0.92	1.05	0.27	0.76	0.61	0.77	0.62	1.07	1.25	-0.05
65	0.48	1.04	0.55	0.27	0.31	0.28	0.57	0.23	-0.01	0.24	0.18
70	0.54	-0.35	-0.19	-0.2	0.39	0.39	0.49	-0.18	0.33	0.35	0.04
75	0.37	0.07	-0.33	-0.12	0.08	-0.04	-0.54	-0.39	0.14	0.26	0.16
80	-0.27	0.18	-0.28	-0.06	-0.15	0.5	0.38	-0.25	0.94	-0.27	0.05
85	-0.23	-0.07	0.05	-0.04	-0.38	0.01	-0.97	-0.13	0.61	0.06	0.19
90	0.14	-0.33	0.05	-0.12	-0.05	0.41	-0.37	0.15	0.11	-0.13	-0.36
95	0.36	-0.28	0.45	-0.21	0.07	0.46	-0.19	-0.32	0.53	0.88	-0.78
100	0.11	0.13	0.29	-0.08	0.4	0.65	0.37	-0.55	-0.07	0.13	0.07
105	0.28	0.03	-0.09	0.33	0.81	0.17	-0.01	0.04	-0.28	0.05	-0.14
110	-0.19	-0.23	-0.36	0.09	0.16	0.02	0.23	0.2	-0.18	0.13	-0.66
115	-0.19	-0.16	0.85	0.54	0.23	-0.03	0.05	0.15	-0.5	-0.03	0.55
120	0.53	0.76	-0.01	-0.16	0.58	-0.11	0.05	0.59	0.42	0.36	0.73
125	0.1	0.67	0.56	0	0.25	0.89	0.6	0.42	1.03	0.44	0.48
130	0.54	0.69	0.98	0.34	0.16	0.58	1.03	0.61	0.74	0.52	0.56

Luminaire

Lamp

No. of lamps	1	Voltage (V)	24	Report
Lamp flux (lm)	205	Current (A)	0.11	Operator
Total flux (lm)	205	Power Factor	1	Date 2021-08-04 오후 2:16:10

Luminous Intensity Data (Continued)

Maximum (cd) : 432

Minimum (cd) : -1

G/C	275	280	285	290	295	300	305	310	315	320	325
0	413.8	407.21	412.47	411.31	412.92	412.22	414.85	414.09	416.02	412.65	415.7
5	383.78	379.38	379.6	373.31	374.13	371.08	373.22	368.26	373	370.63	370.26
10	323.49	322.17	319.2	312.99	314.01	309.65	310.85	307.25	310.75	306.46	308.71
15	256.25	248.28	248.03	244.61	243.01	239.04	240.85	239.67	235.32	236.06	238.52
20	182.57	175.67	176.28	171.93	171.86	167.17	169.13	166.47	167.97	165.56	168.18
25	110.37	106.25	105.72	102.29	103.58	99.49	101.73	99.69	100.79	100.08	102.81
30	49.79	46.45	46.51	43.73	44.69	42.6	43.26	42.13	43.55	41.86	45.21
35	23.09	20.98	20.37	18.71	18.26	17.94	18.31	17.36	17.86	16.84	18.25
40	11.25	10.21	9.82	9.13	9.19	9.12	8.06	8.05	7.83	8.86	8.52
45	5.57	4.58	5.03	4.77	5.16	4.1	4.52	3.82	4.28	4.34	4.05
50	1.92	2.47	1.98	2.02	2.87	1.99	2.36	2.23	2.15	2.21	1.68
55	1.26	1.01	1.76	1.64	1.72	1.06	0.72	1.55	1.33	1.27	1.57
60	0.43	0.55	0.18	0.72	0.31	0.47	1.13	0.52	0.25	0.9	0.47
65	-0.41	0.72	-0.1	-0.45	-0.11	-0.36	0.24	-0.01	0.41	0.2	-0.14
70	-0.54	0.29	-0.46	0.25	-0.12	0.02	0.25	-0.09	0.82	-0.58	0.47
75	0.4	-0.08	0.61	-0.01	0.27	-0.27	0.48	0.21	-0.56	-0.27	-0.31
80	-0.19	0.44	0.34	0.14	-0.13	0.06	0.26	-0.02	-0.24	-0.51	0.1
85	0.08	-0.25	-0.16	0.09	0.25	0.18	0.35	0.2	-0.03	0.53	0.08
90	0.04	-0.55	-0.04	-0.27	-0.24	-0.29	0.26	0.07	0.21	-0.25	0.1
95	-0.51	-0.12	0.6	-0.06	0.06	-0.3	0.21	0.1	0.31	-0.08	0.41
100	-0.45	-0.07	0.27	-0.06	-0.33	0.39	0	0.17	0.09	-0.26	0.31
105	0.11	-0.4	0.25	0.49	-0.04	0.51	0.15	-0.16	-0.08	0.05	0.14
110	0.12	0.26	0.12	0.21	-0.19	0.08	0.35	-0.33	0.53	0.14	1.12
115	-0.05	0.52	0.36	0.28	0.23	0.28	-0.24	0.86	0.13	0.57	0.28
120	0.86	0.36	0.4	0.01	0.73	0.29	0.75	0.35	0.68	0.34	0.7
125	0.39	0.09	0.29	0.19	0.39	0.26	0.53	0.68	0.24	0.77	-0.14
130	0.24	0.33	1	1.05	0.85	0.78	0.69	1.14	0.89	0.82	0.46

Luminaire

Lamp

No. of lamps	1	Voltage (V)	24	Report
Lamp flux (lm)	205	Current (A)	0.11	Operator
Total flux (lm)	205	Power Factor	1	Date 2021-08-04 오후 2:16:10

Luminous Intensity Data (Continued)

Maximum (cd) : 432

Minimum (cd) : -1

G/C	330	335	340	345	350	355	360
0	413.97	415.58	413.48	416.89	414.39	414.64	414.99
5	369.94	370.73	369.43	373.57	373.02	375.27	370.64
10	307.48	310.88	309.34	313.68	311.36	316.9	308.23
15	236.36	239.54	238.53	241.92	242.41	245.9	235.1
20	165.85	169.27	168.08	170.27	171.18	175.62	163.07
25	102.65	105.79	104.76	108.5	108.28	110.72	100.14
30	43.8	46.33	46.59	49.57	48.26	51.29	42.5
35	17.79	18.25	18.37	19.68	19.43	21.32	18
40	8.29	8.62	9.46	9.44	9.1	10.07	9.87
45	4.38	4.36	5.65	5.5	4.23	5.76	5.08
50	2.29	2.73	2.13	2.72	2.89	1.77	2.61
55	1.45	1.19	1.85	0.85	1.2	1.36	1.15
60	0.32	0.32	1.34	0.09	1.2	0.2	0.05
65	0.37	-0.02	0.92	0.54	0.08	0.38	0.41
70	0.32	-0.1	-0.05	0.18	0.08	-0.1	0.12
75	0.01	-0.93	-0.29	0.33	-0.04	0.08	-0.17
80	-0.07	-0.25	0.47	0.39	0.19	0.24	0.12
85	0.11	-0.14	0.2	0.24	-0.6	-0.06	0.36
90	0.16	0.05	0	0.55	0.14	-0.04	0.19
95	-0.15	-0.24	-0.01	-0.56	0.15	0.12	0.21
100	-0.16	0.18	-0.59	0.61	-0.71	0.13	0.99
105	1.1	0.31	0.32	0.7	0.18	-0.04	0.42
110	0.21	0.81	0.42	0.63	-0.34	-0.06	0
115	0.35	0.87	-0.18	0.03	-0.25	-0.26	0.02
120	0.1	0.57	0.22	-0.04	-0.09	0.14	-0.09
125	0.17	0.89	0.44	0.56	0.07	0.48	0.32
130	0.3	0.56	0.51	0.14	0.84	0.8	0.52



Luminaire		Report		
Lamp				
No. of lamps	1	Voltage (V)	24	Filename 210804 DVP-24V-C90-R-5000K.jdt
Lamp flux (lm)	205	Current (A)	0.11	Operator
Total flux (lm)	205	Power Factor	1	Date 2021-08-04 오후 2:16:10

Luminous Flux Table

Total Lamp Lumens: 205



Luminaire Efficiency (lm/W): 204.98

CIE Classification: Direct

Elevation	Lumens	Cumulative	Lamp %	Luminaire %
0	2.47	2.47	1.20	1.20
5	18.98	21.45	10.46	10.46
10	33.72	55.16	26.91	26.91
15	40.74	95.90	46.78	46.78
20	39.35	135.25	65.98	65.98
25	31.06	166.31	81.13	81.13
30	18.05	184.36	89.93	89.94
35	9.39	193.75	94.51	94.52
40	5.17	198.92	97.03	97.04
45	2.72	201.64	98.36	98.37
50	1.33	202.98	99.01	99.02
55	0.69	203.67	99.35	99.36
60	0.40	204.06	99.54	99.55
65	0.21	204.27	99.64	99.65
70	0.06	204.33	99.67	99.68
75	-0.01	204.32	99.67	99.68
80	0.01	204.33	99.67	99.68
85	-0.01	204.32	99.67	99.68
90	-0.01	204.31	99.66	99.67
95	0.01	204.32	99.67	99.68
100	0.03	204.35	99.68	99.69
105	0.05	204.40	99.71	99.72
110	0.07	204.47	99.74	99.75
115	0.09	204.56	99.78	99.79
120	0.13	204.69	99.85	99.86
125	0.17	204.86	99.93	99.94
130	0.12	204.98	99.99	100.00

Luminaire			Report
Lamp			
No. of lamps	1	Voltage (V)	24
Lamp flux (lm)	205	Current (A)	0.11
Total flux (lm)	205	Power Factor	1
		Operator	
		Date	2021-08-04 오후 2:16:10

IsoCandela (Type C)



Luminaire

Lamp

No. of lamps 1

Voltage (V) 24

Report

Lamp flux (lm) 205

Current (A) 0.11

Operator


Total flux (lm) 205

Power Factor 1

Date

2021-08-04 오후 2:16:10

IsoLux Diagram (Ground)



Pole Height (m): 2.7

Area Width (m): 12

Total Optical Solution Provider

Luminaire

Lamp

No. of lamps 1

Voltage (V) 24

Report

Lamp flux (lm) 205

Current (A) 0.11


Filename 210804 DVP-24V-C90-R-5000K.jdt

Total flux (lm) 205

Power Factor 1

Operator

Date 2021-08-04 오후 2:16:10

IsoLux Diagram (Wall)

Luminaire

Lamp

No. of lamps 1 Voltage (V) 24
 Lamp flux (lm) 205 Current (A) 0.11
 Total flux (lm) 205 Power Factor 1

Report

Filename 210804 DVP-24V-C90-R-5000K.jdt


Operator

Date 2021-08-04 오후 2:16:10

Illuminance Levels (Ground)

6.00	0.00	0.00	0.00	0.00	0.00	0.01	0.01	0.01	0.01	0.00	0.00	0.00	0.00	0.00
5.00	0.00	0.00	0.01	0.01	0.01	0.02	0.03	0.02	0.01	0.00	0.01	0.00	0.00	0.00
4.00	0.00	0.01	0.00	0.02	0.02	0.07	0.08	0.06	0.01	0.01	0.01	0.00	0.00	0.00
3.00	0.00	0.01	0.02	0.03	0.07	0.17	0.24	0.11	0.05	0.02	0.01	0.01	0.00	0.00
2.00	0.01	0.01	0.03	0.08	0.71	1.31	4.75	0.80	0.40	0.04	0.01	0.00	0.00	0.00
1.00	0.01	0.03	0.08	0.18	1.40	11.73	34.43	8.00	0.63	0.09	0.04	0.01	0.00	0.00
0.00	0.02	0.03	0.11	0.33	6.19	39.61	56.93	26.07	2.49	0.15	0.06	0.01	0.00	0.00
-1.00	0.01	0.03	0.09	0.16	1.37	10.18	28.62	6.72	0.58	0.10	0.05	0.01	0.00	0.00
-2.00	0.01	0.01	0.03	0.08	0.63	1.03	2.98	0.62	0.31	0.05	0.01	0.01	0.00	0.00
-3.00	0.00	0.01	0.02	0.02	0.06	0.13	0.15	0.09	0.04	0.02	0.02	0.00	0.00	0.00
-4.00	0.00	0.01	0.01	0.02	0.02	0.06	0.06	0.04	0.02	0.01	0.00	0.00	0.00	0.00
-5.00	0.00	0.00	0.01	0.01	0.01	0.02	0.01	0.01	0.00	0.00	0.00	0.00	0.00	0.00
-6.00	0.00	0.00	0.00	0.00	0.00	0.01	0.00	0.01	0.00	0.00	0.00	0.00	0.00	0.00
-6.00	-5.00	-4.00	-3.00	-2.00	-1.00	0.00	1.00	2.00	3.00	4.00	5.00	6.00		

Illum. (Max.) : 56.9



Illum. (Min.) : 0.00



Illum. (Avg.) : 1.49

All illuminance level values are in lux.

Luminaire

Lamp

No. of lamps 1

Voltage (V) 24

Report

Lamp flux (lm) 205

Current (A) 0.11

Filename 210804 DVP-24V-C90-R-5000K.jdt

Total flux (lm) 205


Power Factor 1

Operator

Date

2021-08-04 오후 2:16:10

Illuminance Cone Diagram





Luminaire

Lamp

No. of lamps 1

Voltage (V) 24

Lamp flux (lm) 205

Current (A) 0.11

Total flux (lm) 205

Power Factor 1

Report

Filename 210804 DVP-24V-C90-R-5000K.jdt

Operator

Date 2021-08-04 오후 2:16:10

Coefficient of Utilization

	Refl.	Ceiling (%)	80%	80%	80%	70%	70%	70%	50%	50%	50%	30%	30%	30%	10%	10%	10%	0%
	Refl.	Wall (%)	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0%
Eff. Floor Cavity	Refl.	20%	20%	20%	20%	20%	20%	20%	20%	20%	20%	20%	20%	20%	20%	20%	20%	20%
Room CR 0	0	1.28	1.28	1.28	1.25	1.25	1.25	1.19	1.19	1.19	1.14	1.14	1.14	1.09	1.09	1.09	1.07	
Room CR 1	1	1.20	1.18	1.15	1.18	1.16	1.14	1.13	1.12	1.10	1.09	1.08	1.07	1.06	1.05	1.04	1.02	
Room CR 2	2	1.13	1.09	1.06	1.11	1.08	1.05	1.08	1.05	1.02	1.04	1.02	1.00	1.01	1.00	0.98	0.96	
Room CR 3	3	1.07	1.02	0.98	1.05	1.01	0.97	1.02	0.99	0.96	1.00	0.97	0.94	0.97	0.95	0.93	0.91	
Room CR 4	4	1.01	0.96	0.92	1.00	0.95	0.91	0.97	0.93	0.90	0.95	0.92	0.89	0.93	0.90	0.88	0.87	
Room CR 5	5	0.96	0.90	0.86	0.95	0.90	0.86	0.93	0.88	0.85	0.91	0.87	0.84	0.89	0.86	0.84	0.82	
Room CR 6	6	0.91	0.85	0.81	0.90	0.85	0.81	0.89	0.84	0.81	0.87	0.83	0.80	0.86	0.82	0.80	0.78	
Room CR 7	7	0.87	0.81	0.77	0.86	0.81	0.77	0.85	0.80	0.77	0.83	0.79	0.76	0.82	0.79	0.76	0.74	
Room CR 8	8	0.83	0.77	0.73	0.82	0.77	0.73	0.81	0.76	0.73	0.80	0.76	0.73	0.79	0.75	0.72	0.71	
Room CR 9	9	0.79	0.74	0.70	0.79	0.73	0.70	0.78	0.73	0.70	0.77	0.72	0.69	0.76	0.72	0.69	0.68	
Room CR 10	10	0.76	0.70	0.67	0.75	0.70	0.67	0.74	0.70	0.66	0.74	0.69	0.66	0.73	0.69	0.66	0.65	