

DATE PROJECT LOCATION TYPE



PRODUCT FEATURES

- Ultra Slim Profile
- Single Diode Provides Single Crisp Image
- Linkable Units (Link up to 7 units together)
- Recessed or Surface Mount
- Control with 0-10V, DALI, DMX, Zigbee

PRODUCT SPECIFICATIONS

Power Input	24V DC Constant Voltage
Color Rendering Index	CRI>90
Available CCTs	2700K, 3000K, 3500K, 4000K
Energy Efficiency	100lm/W
Operating Temperature Ranges	0-45°C (32-113°F)
Control	0-10V, DALI, DMX, Zigbee
Finish	Black, White, Silver (Special Order Option- Bronze)
Beam Angle	60° (STD), 25° and 45° (Special Order Option)
Lamp Life	50,000hr / 70%
Warranty	5 year
Note	Product is approved for Closet / Storage space installation per NEC410.16 (A) (3) and NEC410.16 (C)(5) per NRTL certification

SPECIFICATION



Performance data shown below for 4000K CCT. Refer to individual luminaire IES files for other CCT options.

Model Name	Power Input	Lamp Power	Luminous Flux	Luminous Efficacy	Color Rendering Index	Color Temperature	Beam Angle	Operating Temperature
DVS4A (color)K-24V-25	DC 24V	4.5 W	487 lm	108 lm/w	CRI > 90	2700K, 3000K, 3500K, 4000K	25° *	0-45°C (32-113°F)
DVS4A (color)K-24V-45		4.6 W	502 lm	109 lm/w	CRI > 90		45° *	
DVS4A (color)K-24V-60		4.6 W	493 lm	107 lm/w	CRI > 90		60°	

* 25 or 45 degree are special options


SPECIFICATION GUIDE

NOT TO BE USED FOR ORDERING. The Specification Guide is intended solely to ensure that all options are considered.


MODEL	COLOR	BEAM ANGLE	FINISH	MOUNTING	DRIVER	CONTROLS	VOLTAGE
DVS4A	27K -2700K 30K -3000K 35K -3500K 40K -4000K	C90 25° 45° 60°(STD)	BK - Black WT - White SV - Silver (Special Order Option) BZ - Bronze (Special Order Option)	RM - Recessed Mount RMS - Recessed Mount Spring SM - Surface Mount	CP - Cable/Plug HW - Hard Wire TD - 3rd Party Drivers Consult Factory	NDM - Non-Dim 0-10V DALI - DALI Interface DMX - DMX Interface	120V 230V 277V

DIMENSION


*Recessed Mount



*Recessed Mount Spring




*Surface mount ring




INSTALLATION


FLX Spot DVS & FLX Spot DVS




Hole Diameter




Mounting spring installation



FLX Spot DVS & FLX Stix NDP




FLX Stix NDP & FLX Spot DVS




★ Linkabel between FLX Spot DVS and FLX Spot DVS
(Max. 7 units connectable in a row/LED Driver)

BEAM SPREADS


DVS4A 40K-24V-25



DVS4A 40K-24V-45



DVS4A 40K-24V-60



COMPONENTS




FLX Spot DVS

- __DVS4A (color)K-24V-WT
- __DVS4A (color)K-24V-BK
- __DVS4A (color)K-24V-SV
- Other finishes available as special order



Dimming Interface (0-10V)

- __FDC-L10 *
- Max. 100W (100W/CH, 1CH)



12 Port Hub

- __D12P-HUB
- Included with Cord and Plug drivers. Order separately for Hard Wire or 3rd Party Drivers



Extension cable

- __DVSPTC
- (2,500mm/98.43")




Control Interface (0-10V)

- __FDD-L20
- Max. 200W (100W/CH, 2CH)



LED Drivers

- __FLC30-24V/XL (30W) *
- __FLC75-24V/XL (75W) *
- With distributor and power cord 1800mm (6')




Connecting cable

- __NDPVSPTC
- (1,000mm/39.37")
- For Linking Linear Fixtures




Control Interface (DALI)

- __FDD-L1DA
- Max. 200W (100W/CH, 1CH)



Driver Junction Box

- __MHWB-FLE



Connecting cable

- __NDVPC
- (2,500mm/98.43")
- For Linking Linear Fixtures




Control Interface (0-10V, DMX512)

- __FDA-L2MO
- Max. 200W (100W/CH, 2CH)
- __FDA-L5M
- Max. 200W (50W/CH, 5CH)



Hard Wire Driver

- __XLD200-224V-FCL-DIM (0-10V)
- __XLD75-124V-FC *
- (90V to 300V)



Connecting cable

- __NDPPC
- (2,500mm/98.43")
- For Linking Linear Fixtures




Control Interface (Zigbee)

- __FDD-L2Z

A larger selection of drivers are available including remote and hard wire drivers. Please consult factory.

* FLC30, FLC75 and XLD75 require the FDC-L10 for 0-10V dimming



Mounting spring

- __DVS spring
- Other finishes available as special order



Wireless Control (Zigbee Switch)

- __FSM-Z1



Surface mount ring

- __DVS MR-WT
- __DVS MR-BK
- __DVS MR-SV
- Other finishes available as special order



Door and motion sensor

- __FLS-M24V



Deco Ring

- __DVS DR-WT
- __DVS DR-BK
- __DVS DR-SV
- Other finishes available as special order



Occupancy sensor

- __FLS-P24V